

# M.V. Arklow Future



Port of Registry	Arklow	Yard	Astilleros de Murueta SA, Spain
Call Sign	EIGD5	Year of Build	2008
IMO No.	9361768	Class	Bureau Veritas
MMSI No.	250001594	Class Notation	I+HULL,+MACH, GRL CARGO SHIP, HEAVY CARGO UNRESTRICTED NAVIGATION + AUT-UMS + STRENGTHBOTTOM, +INWATER SURVEY+MON-SHAFT
Inmarsat-C (Telex)	+(581) 425000259 +(581) 425000260	Class No.	09716N
Email	425000259@stratosmobile.net	Official No.	404065
GSM telephone (Irish)	+ 353 (0) 87 6693113		



## Principal Particulars

Length OA	89.95m	<b>Hold Capacity: Grain &amp; Bale</b>	<b>Main Engine:</b>
Length BP	84.98m	(incl. B/H) 213,855.53 ft <sup>3</sup> / 6,056 m <sup>3</sup>	MaK 6M25 1980kW with Reinjtes Gearbox and controllable pitch propeller
Breadth Mld	14.4m	(excl. B/H) 214,491.16 ft <sup>3</sup> / 6,074 m <sup>3</sup>	<b>Auxiliaries:</b>
Breadth Ext	14.5m	Portable bulkheads (2) may be placed in	2 x Guascor SH74TAB-SG 175kW
Depth Mld	7.35m	10 positions for cargo separation	1 x Guascor H33TSG 50kW
Summer Load Draft	6.28m	<b>Hatches:</b> Roden Staal pontoon system	<b>Generators:</b>
Min. airdraft is	21.70m	Maximum hatch top loading 1.75t/m <sup>2</sup>	2 x Stamford HCM434C2, 190kva, 1500rpm
at max. ballast draft of	3.8m	Maximum tank top loading 15t/m <sup>2</sup>	1 x Stamford UCM224G2, 60kva, 1500rpm
min. coaming height above waterline	5.6m	Bottom strengthened for loading aground	1 x shaft alternator Stamford HCM534C2
GT	2998	Tank top strengthened for heavy cargoes	<b>Speed:</b> abt. 11.5knots
NT	1673	Engine room bulkhead A60 insulated	<b>Consumption:</b>
Displacement	5941t	CO <sub>2</sub> fire extinguishing system in hold	In port – abt. 0.75t Gas Oil per day
Total Deadweight	4480t	Engine room fitted with CO <sub>2</sub> and flexi-fog	At sea – abt. 7.50t HFO per day
Ballast	2030t	Certified for the carriage of dangerous	<b>Equipment:</b> GMDSS (A3), 2x radars, AP, navtex, echosounder, speed/distance log, 2 x GPS receivers, gyro/magnetic compasses, electronic charts, 1 x electric bowthruster 250kW.
Fuel (HFO)	182t	goods of IMO Class 4.1, 4.2, 4.3, 5.1	
Fuel (GO)	37t	and 5.2 (packaged)	
Fresh Water	46.8t		
Lub Oil	12.1t		

07/12/2010

E. & O. E.

# ARKLOW FUTURE

