STATEMENT OF COMPLIANCE FOR CARRIAGE OF CARGO IN BULK

No LDR0/SMC/20210723184251

Issued within the scope of the Bureau Veritas Marine & Offshore General Conditions.

| Name of Ship BV No : 29096D | Distinctive Number or Letters | Port of Registry | Gross Tonnage | IMO Number |
|---------------------------------------|-------------------------------|------------------|---------------|------------|
| ARKLOW CADET | EIRP3 | ARKLOW | 2999 | 9757084 |

THIS IS TO CERTIFY:

That the ship is classed with the Society and can carry in solid bulk cargo as specified in Appendix 1 in compliance with the International Maritime Solid Bulk Cargoes (IMSBC) Code as amended by resolution MSC.462(101) and SOLAS 74, Regulations II-2/19 as applicable, provided that the ship is loaded in accordance with the said Regulations to the Master's satisfaction.

This Statement of Compliance is valid until 14 July 2026 subject to the conditions allowing its issuance remain unchanged.

Completion date of the survey on which this Statement is based: 25 June 2021

Issued at FOYNES, on the 23 July 2021

VERITAS

BUREAU VERITAS
VARINE & OFFSHORE

Connell

By Order of the Secretary

The latest published Rules of the Bureau Veritas Marine & Offshore, and the General Conditions therein, are applicable.

La dernière édition des Règlements de Bureau Veritas Marine & Offshore, ainsi que les Conditions Générales qui y figurent, sont applicables.

Any person not a party to the contract pursuant to which this document is delivered may not assert a claim against Bureau Veritas Marine & Offshore for any liability arising out of errors or omissions which may be contained in said document, or for errors of judgement, fault or negligence commited by personel of the Society or its Agents in the establishment or issuance of this document, and in connection with any activities for which it may provide.

Toute personne qui n'est pas partie au contrat aux termes duquel ce document est délivré ne pourra engager la responsabilité du Bureau Veritas Marine & Offshore pour les inexactitudes ou omissions qui pourraient y être relevées ainsi que pour les erreurs de jugement, fautes ou négligences commises par le personnel de la Société ou par ses agents dans l'établissement de ce document et dans l'exécution des interventions qu'il comporte.

STATEMENT OF COMPLIANCE No: LDR0/SMC/20210723184251

NAME OF SHIP

: ARKLOW CADET

BV REGISTER

: 29096D

Additional remarks (if any):

Carriage requirements of individual schedules of solid bulk cargoes apply.

STATEMENT OF COMPLIANCE No: LDR0/SMC/20210723184251

NAME OF SHIP : ARKLOW CADET

BV REGISTER

: 29096D

See attached list of Classes/Products in annex.

APPENDIX 1 TO STATEMENT OF COMPLIANCE LIST OF CARGOES

STATEMENT OF COMPLIANCE No: LDR0/SMC/20210723184251

NAME OF SHIP : ARKLOW CADET

BV REGISTER: 29096D

Caption used in the next table(s) for the carriage of goods:

Y indicates CARGO ALLOWED X indicates NOT ALLOWED

| CARGO SHIPPING NAME | UN No | CLASS | GROUP | Cargo Hold |
|--|-------|-------------|---------|-------------------|
| Alfalfa | | | С | Y 28 |
| Alumina | | | С | Y |
| Alumina hydrate | | MHB | A and B | Υ |
| Alumina silica | | | С | Υ |
| Alumina silica, peliets | | | С | Υ |
| Alumina, calcinated | | | С | Υ |
| Alumínium Ferrosilicon powder | 1395 | 4.3 sub 6.1 | В | Y 1, 2 |
| Aluminium fluoride | | | Α | Υ |
| Aluminium nitrate | 1438 | 5.1 | В | Υ |
| Aluminium silicon powder, uncoated | 1398 | 4,3 | В | Y 1, 2 |
| Aluminium smelting /remeiting by products, processed | | мнв | A and B | Y 1, 3 |
| Aluminium smelting by-products or aluminum remelting by products | 3170 | 4.3 | В | Y 1, 2 |
| Ammonium nitrate | 1942 | 5.1 | В | Y 1, 4 |
| Ammonium nitrate based fertilizer | 2067 | 5.1 | 8 | Y _{1, 4} |
| Ammonium nitrate based fertilizer | 2071 | 9 | В | Y 1,5 |
| Ammonium nitrated based fertilizer (non hazardous) | | | С | Υ |
| Ammonium sulphate | | | С | Υ |
| Amorphous sodium silicate lumps | | MHB (CR) | В | Υ |
| Antimony ore and residue | | | С | Υ |
| Barityes | | | С | Y |
| Barium nitrate | 1446 | 5.1 sub 6,1 | В | Υ |
| Bauxite | | | С | Υ |
| Bauxite fines | | | Α | Υ |
| Biosludge | | | С | Υ |
| Borax (pentahydrate crude) | | | С | Υ |
| Borax, anhydrous | | | С | Υ |
| Boric acid | | MHB (TX) | В | Υ |
| Brown coal briquettes | | мнв | В | Y 1 |
| frucite | | | С | Y |
| alcium fluoride, Calcium sulphate, Calcium arbonate mixture | | | A | Y |
| alcium nitrate | 1454 | 5.1 | В | Υ |
| alcium nitrate fertilizer | | | С | Y |

BV REGISTER : 29096D

| CARGO SHIPPING NAME | UN No | CLASS | GROUP | Cargo Hold |
|---|-------|-------|----------|-----------------|
| Carborundum | | | С | Y |
| Castor Beans or castor meal or castor pomace or castor flake | 2969 | 9 | В | Υ 6 |
| Cement | | | С | Υ |
| Cement clinkers | | | С | Υ |
| Chamotte | | | С | Υ |
| Charcoal | | MHB | В | Y 7 |
| Chemical gypsum | | | Α | Y |
| Chlorite | | | С | Υ |
| Chopped rubber and plastic insulation | | | С | Y ₈ |
| Chrome pellets | | | С | Υ |
| Chromite ore | | | С | Υ |
| Clay | | | С | Υ |
| Clinker ash | | MHB | A and B | Υ |
| Coal | | MHB | B(and A) | Y 1 |
| Coal slurry | | | Α | Υ |
| Coal tar pitch | | MHB | В | Υ |
| Coarse chopped tyres | | | С | Y ₉ |
| Coarse iron and steel slag and its mixture | | | С | Υ |
| Coke | | | С | Y |
| Coke breeze | | | Α | Υ |
| Colemanite | | | С | Υ |
| Copper granules | | | С | Υ |
| Copper matte | | | С | Υ |
| Copper slag | | | Α | Y |
| Copra (dry) | 1363 | 4.2 | 8 | Y ₁₀ |
| Crushed carbon anodes | | | С | Y |
| Cryolite | | | С | Υ |
| Diammonium Phosphate (D.A.P) | | | С | Y |
| Direct reduced iron (A) Briquettes, hot-moulded | | MHB | В | Y 1, 11 |
| Direct reduced iron (B) Lumps, pellets, cold-moulded briquettes | | МНВ | В | Y 1, 12 |
| Direct reduced iron (C) (By-products fines) | | MHB | В | Y 1, 12 |
| Distillers dried grains with solubles | | | С | Υ |
| Dolomite | | | С | Y |
| Felspar lump | | | С | Υ |
| Ferrochrome | | | С | Y |
| Ferrochrome, exothermic | | | С | Υ |
| Ferromanganese | | | С | Υ |
| Ferronickel | | | С | Y |

BV REGISTER : 29096D

| CARGO SHIPPING NAME | UN No | CLASS | GROUP | Cargo Hold |
|--|-------|--------------------|---------|--------------------|
| Ferronickel slag (granulated) | | | С | Υ |
| Ferrophosphorus (including briquettes) | | MHB | В | Υ 1 |
| Ferrosilicon with 25% to 30% silicon or 90% or more silicon (including briquettes) | | МНВ | В | Y _{1, 14} |
| Ferrosilicon with 30% or more but less than 90% silicon (including briquettes) | 1408 | 4.3 sub 6.1 | В | Y _{1, 13} |
| Ferrous metal borings, shavings, turning or cuttings | 2793 | 4.2 | В | Υ |
| Ferrous sulphate heptahydrate | | | С | Υ |
| Fertilizers without nitrates (non-hazardous) | | | С | Υ |
| Fish (in bulk) | | | Α | Υ |
| Fishmeal (fishcrap), stabilized | 2216 | 9 | В | Y 15 |
| Flue dust, containing lead and zinc | | MHB (TX and/or CR) | A and B | Υ |
| Fluorspar | | MHB | A and B | Y |
| Fly ash, dry | | | С | Υ |
| Fly ash, wet | | | A | Y |
| Foam glass gravel | | | С | Y |
| Glass cullet | | | С | Υ |
| Grain screening pellets | | | С | Y 16 |
| Granular ferrous sulphate | | | С | Y |
| Granulated nickel matte (less than 2% moisture content) | | МНВ | В | Υ |
| Granulated slag | | | С | Y |
| Granulated tyre rubber | | | С | Y ₁₇ |
| Эурэит | | | С | Y |
| Sypsum granulated | | | С | Y |
| Imenite (rock) | | | С | Υ |
| lmenite (upgraded) | | | Α | Υ |
| lmenite clay | | | A | Υ |
| imenite sand | | | A or C | Υ |
| ron and steel slag and its mixture | | | A | Y |
| ron ore | | | С | Υ |
| ron ore fines | | | Α | Υ |
| ron ore pellets | | | С | Υ |
| ron oxide technical | | | A | Υ |
| ron oxide, spent or iron sponge, spent | 1376 | 4.2 | В | Y 18 |
| ron sinter | | | С | Υ |
| on smelting by-products | | | С | Y |
| ronstone | | | С | Y |
| abradorite | | | С | Υ |
| ead nitrate | 1469 | 5.1 sub 6.1 | В | Υ |

BV REGISTER: 29096D

| CARGO SHIPPING NAME | UN No | CLASS | GROUP | Cargo Hold | |
|--|-------|-----------------------|---------|-----------------|--|
| Lead ore | | | С | Υ | |
| Lime (unslaked) | | MHB | В | Υ | |
| Limestone | | | С | Υ | |
| Linted cotton seed with no more than 9% moisture and not more than 20.5% oil | | MHB | В | Υ | |
| Magnesia (deadburned) | | | С | Y ₁₉ | |
| Magnesia (unslaked) | | MHB | В | Υ | |
| Magnesite, natural | | | С | Υ | |
| Magnesium nitrate | 1474 | 5,1 | В | Y | |
| Magnesium sulphate fertilizers | | | С | Υ | |
| Manganese componenent ferroalloy slag | | | С | Υ | |
| Manganese ore | | | С | Υ | |
| Manganese ore fines | | | Α | Υ | |
| Marble chips | | | С | Υ | |
| Matte containing copper and lead | | MHB (TX and/or CR) | В | Υ | |
| Metal sulphide concentrate | | MHB | A and B | Υ | |
| Metal sulphide concentrates, corrosive | 1759 | 8 | A and B | Υ | |
| Metal sulphide concentrates, self-heating | 3190 | 4.2 | A and B | Υ | |
| Mineral concentrates | | | Α | Y | |
| Monoammonium phosphate (M.A.P) | | | С | Y | |
| Monoammonium phosphate (M.A.P), mineral enriched coating | | MHB (CR) | В | Y | |
| Monocalciumphosphate (MCP) | | MHB(CR) | A and B | Υ | |
| Nickel ore | | | Α | Y | |
| Olivine granular and gravel aggregate products | | | С | Υ | |
| Olivine sand | | | Α | Υ | |
| Peanuts (in shell) | | | С | Υ | |
| Peat moss | | MHB | A and B | Υ | |
| Pebbles (sea) | | | С | Υ | |
| Pellets (concentrate) | | | С | Y | |
| Perlite rock | | | С | Υ | |
| Petroleum coke (calcined or uncalcined) | | MHB | В | Υ | |
| Phosphate (defluorinated) | | | С | Υ | |
| Phosphate rock (calcinated) | | | С | Υ | |
| Phosphate rock (uncalcinated) | | | С | Υ | |
| Pig iron | | | С | Y | |
| Pitch prill | | MHB | В | Υ | |
| Potash | | | С | Υ | |
| Potassium chloride | | | С | Υ | |
| Potassium nítrate | 1486 | 5.1 | В | Y | |

BV REGISTER : 29096D

| CARGO SHIPPING NAME | UN No | CLASS | GROUP | Cargo Hold |
|---|----------------------------|-------|---------|--------------------|
| Pumice | (A.C. (Mariano - N. (1997) | | С | Y |
| Pyrite (containing copper and iron) | | | С | Υ |
| Pyrites, calcinated (calcinated pyrites) | | MHB | A and B | Υ |
| Pyrophyllite | | | С | Υ |
| Quartz | | | С | Y |
| Quartzite | | | С | Υ |
| Radioactive material, low specific activity (LSA-1), non fissile or fissile-excepted | 2912 | 7 | В | Х |
| Radioactive material, surface contaminated objects (SCO-I), non fissile or fissile-excepted | 2913 | 7 | В | Х |
| Rasorite (anhydrous) | | | С | Y |
| Rutile sand | | | С | Υ |
| Salt | | | С | Υ |
| Salt cake | | | С | Υ |
| Salt rock | | | С | Υ |
| Sand | | | С | Υ |
| Sand, heavy mineral | | | Α | Y |
| Sand, mineral concentrate, radioactive material, ow specific activity (LSA-I) | 2912 | 7 | A and B | Χ |
| Sawdust | | МНВ | В | Y 20 |
| Scale generated from the iron and steel making process | | | А | Υ |
| icrap metal | | | С | Y |
| seed cake with not more than 1.5% oil and not more than 11% moisture | 2217 | 4.2 | В | Y 1, 21 |
| seed cake, containing vegetable oil (a), nechanically expelled seeds, containing more han 10% of oil or more than 20% of oil and noisture combined | 1386 | 4.2 | В | Y |
| seed cake, containing vegetable oil (b) solvent xtractions and expelled seeds, containing not nore than 10% of oil and when the amount of noisture is higher than 10%, not more than 20% of oil and moisture combined | 1386 | 4.2 | В | Y _{1, 21} |
| eed cakes and other residues of processed oily egetables (group B) | | | В | Y 1 |
| eed cakes and other residues of processed oily egetables (group C) | | | С | Y ₂₇ |
| ilicomanganese (carbo-thermic) | | | С | Y |
| ilicomanganese (low carbon) | | MHB | В | Y 1, 22 |
| ilicon slag | | | С | Y |
| oda ash (Dense and light) | | | С | Y |
| odium nitrate | 1498 | 5.1 | В | Y |
| odium nitrate and potassium nitrate mixture | 1499 | 5.1 | В | Y |
| olidified fuels recycled from paper and plastics | | MHB | В | Y 23 |
| podumene (upgraded) | | | A | . 23 |

BV REGISTER: 29096D

| CARGO SHIPPING NAME | UN No | CLASS | GROUP | Cargo Hold |
|--|-------|----------------------------|---------|--------------------|
| Stainless steel grinding dust | | | C | Υ |
| Stone chippings | | | С | Y |
| Sugar | | | С | Υ |
| Sugarcane biomass pellets | | MHB (CB, WT, WF, OH) | В | Y ₂₆ |
| Sulphate of potash and magnesium | | | С | Υ |
| Sulphur (crushed lump and coarse grained) | 1350 | 4.1 | В | Y _{1, 24} |
| Sulphur (formed, solid) | | | С | Υ |
| Superphosphate | | | С | Υ |
| Superphosphate (triple, granular) | | | С | Y |
| Synthetic calcium fluoride | | | Α | Υ |
| Synthetic silicon dioxide | | | Α | Υ |
| Taconite pellets | | | С | Υ |
| Talc | | | С | Υ |
| Tankage | | MHB | В | Υ |
| Tapioca | | | С | Υ |
| Titanomagnetite sand | | | Α | Y |
| Urea | | | С | Υ |
| Vanadium ore | | MHB | В | Υ |
| Vermiculite | | | С | Y ₂₅ |
| White quartz | | | С | Υ |
| Wood pellets containing additives and/or binders | | MHB (WF) | В | Υ |
| Wood pellets not containing any additives and/or binders | | MHB(OH) | 8 | Y |
| Wood produts -general | | МНВ | В | Υ |
| Wood torrefied | | MHB | В | Υ |
| Woodchips | | MHB | В | Υ |
| Zinc ashes | 1435 | 4.3 | В | Y 1 |
| Zinc oxide enriched flue dust | | | A and B | Υ |
| Zinc slag | | | Α | Y |
| Zircon kyanite concentrate | | | Α | Y |
| Zirconsand | | | С | Y |

BV REGISTER: 29096D

Notes applicable for this document:

- (1) Electrical equipment which is not essential for the safety and operation of the ship and which is not of a type approved for use in the considered area shall be: completely disconnected by appropriate means other than fuses at a point external to the space
 - protected against unauthorized re-connection
- (2) Prior to loading this cargo a certificate shall be provided by the manufacturer or shipper stating that, after manufacture, the material was stored under cover, but exposed to the weather in the particle size shipped, for not less than 3 days prior the shipment
- Prior to loading this cargo a weathering certificate shall be provided by the manufacturer or shipper stating that, after manufacturer, the material was stored under cover, but exposed to the weather in the particle size shipped, for not less than 4 WEEKS prior the shipment
- (4) Prior to loading, the shipper shall provide the master with a certificate signed by the shipper stating that all the relevant conditions of the cargo required by this code including its individual schedule have been met. In addition, prior to loading, the shipper shall provide the master with a certificate stating that the resistance to detonation of this
- (5) This cargo shall only be accepted for loading when, as a results of testing in the trough test, its liability to self-sustaining decomposition shows decomposition rate not greater than 0.25m/h
- (6) Castor meal, castor pomace and castor flakes shall not be carried in bulk
- (7) The manufacturer or shipper shall give the master a certificate stating that the cargo is not class 4.2 in accordance with the results of the test approved by the competent authority. The certificate shall also state that this cargo has been weathered for not less than 13 days. This cargo shall only be accepted for loading when the actual moisture content of the cargo is not more than 10%
- (8) Prior to shipment, a certificate shall be given to the master by the shipper stating that this cargo consists of clean plastic and rubber material only.
- (9) Prior to shipment, a certificate shall be given to the master by the shipper stating that this cargo is free of oily products or oily residue and has been stored under cover but in the open air for not less than 15 days prior shipment.
- (10) This cargo shall only be accepted for loading when the cargo has been weathered for at least one month before shipment or when the shipper provides the master with certificate issued by a person recognized by the competent authority of the country of origin stating that the moisture content of the cargo is not more than 5%
- (11) The shipper shall provide the master with a certificate issued by a competent person recognized by the national administration of the port of loading stating that the cargo, at the time of loading, is suitable for shipment and that it conforms with the requirements of IMSBC Code; that the quantity of fines and small particles (up to 6.35 mm in size) is no more than 5% by weight; the moisture content is less than 1.0% and the temperature does not exceed 65°C
- Prior to loading this cargo, the shipper shall provide the master with a certificate issued by a competent person recognized by the national Administration of the port of loading stating that the cargo, at the time of loading, is suitable for shipment, and that it conforms with the requirements of IMSBC Code; that the quantity of fines and small particles is no more than 5% by weight; that the moisture content is less than 0,3%; and that the temperature does not exceed 65°C. This certificate shall state the date of manufacture for each lot of cargo to be loaded in order to meet the loading orderia in regards to ageing and material temperature. Provision shall be made to introduce a dry, 15% throughout the voyage in accordance with the requirements of IMSBC.
- (13) The manufacturer or the shipper shall provide the master with a certificate stating that, after manufacture, the cargo was stored under cover, but exposed to dry weather for not less than three days prior to shipment
- (14) The manufacturer or the shipper shall provide the master with a certificate stating that, after manufacture, the cargo was stored under cover, but exposed to open air for not less than three days prior to shipment.
- (15) The shipper shall provide the master with a certificate issued by a person recognized by the competent authority of the country with the information requested in IMSBC (moisture content, fat content, date of production...)
- (16) A certificate from a person recognized by the competent authority of the country of shipment shall be provided by the shipper to the master, prior to loading, confirming that the oil and moisture contents as described in the schedule have been met
- (17) Prior to shipment, a certificate shall be given to the master by the shipper stating that this cargo consists of clean rubber only
- (18) Prior to loading, the shipper or the manufacturer shall provide the master with a certificate stating that the cargo has been cooled and then weathered for not less than 8 weeks prior to shipment
- Prior to loading, the shipper or the manufacturer shall provide the master with a declaration stating that the cargo has been sufficiently heat-treated and is ready for loading.

 Prior to loading this cargo, the shipper shall provide the master with a declaration stating that the cargo has been sufficiently heat-treated and is ready for loading.
- (20) Prior to loading this cargo, the shipper shall provide the master with a certificate stating that the cargo is clean, dry and free from oil

 This cargo shall only be accepted for loading when the cargo is substatically free from formalists and only be accepted for loading when the cargo is substatically free from formalists and only be accepted for loading when the cargo is substatically free from formalists.
- (21) This cargo shall only be accepted for loading when the cargo is substantially free from flammable solvent and a certificate from a person recognized by the competent authority of the country of shipment specifying the oil content and moisture content is issued.
 (22) The manufacturer or the shipper shall provide the master with a certificate station that affect manufacturer or the shipper shall provide the master with a certificate station that affect manufacturer or the shipper shall provide the master with a certificate station that affect manufacturer or the shipper shall provide the master with a certificate station.
- (22) The manufacturer or the shipper shall provide the master with a certificate stating that, after manufacture, the cargo was stored under cover, but exposed to open air for not less than three days prior to shipment.
 (23) The manufacturer or shipmer shall give the master a certificate stating that the revenience of the cargo was stored under cover, but exposed to open air for not less than three days prior to shipment.
- (23) The manufacturer or shipper shall give the master a certificate stating that the cargo is not class 4.2
 (24) Fine grained sulphur (flower of sulphur) shall not be transported in bulk.
- (24) Fine grained sulphur (flower of sulphur) shall not be transported in bulk
 (25) Prior to loading a certificate based on test shall be provided by the presided by
- (25) Prior to loading, a certificate based on test shall be provided by the manufacturer or shipper stating that the asbestos content is less than 1%
- Close or direct contact of this cargo and cargo hold lighting such as hot halogen lamps shall be avoided. Fuses to such lights shall be removed or secured while this cargo is present in the cargo space
- (27) A certificate from a person recognized by the competent authority of the country of shipment shall be provided by the shipper, prior to loading, stating that the requirements for exclusion from either the schedule for SEED CAKE UN 1386 (b) or UN 2217, whichever is applicable, are met as set out in those schedules and that the material does not meet the MHB (SH) criteria specified in 9.2.3.3.
- (28) Prior to loading of this cargo, a certificate shall be provided by a competent authority or shipper stating that the material as shipped does not meet the requirement for Seed cake

Space identification:

Cargo Hold: Cargo Hold