STATEMENT OF COMPLIANCE FOR CARRIAGE OF CARGO IN BULK No GDA0/EMC/20180823101313

Issued within the scope of the Bureau Veritas Marine & Offshore General Conditions.

Name of Ship BV No: 15277H	Distinctive Number or Letters	Port of Registry	Gross Tonnage	IMO Numbe
ARKLOW MUSE	EINV3	ARKLOW	9758	9509487

THIS IS TO CERTIFY:

That the ship is classed with the Society and can carry in solid bulk cargo as specified in Appendix 1 in compliance with the International Maritime Solid Bulk Cargoes (IMSBC) Code as amended by resolution MSC.426(98) and SOLAS 74, Regulations as applicable, provided that the ship is loaded in accordance with the said Regulations to the Master's satisfaction.

This Statement of Compliance is valid until 21 August 2023 subject to the conditions allowing its issuance remain unchanged.

Completion date of the survey on which this Statement is based: 24 August 2018

Issued at Gdansk, on the 24 August 2018



Jan Dabkowski
By Order of the Secretary

The latest published Rules of the Bureau Veritas Marine & Offshore, and the General Conditions therein, are applicable.

La dernière édition des Règlements de Bureau Veritas Marine & Offshore, ainsi que les Conditions Générales qui y figurent, sont applicables.

Any person not a party to the contract pursuant to which this document is delivered may not assert a claim against Bureau Veritas for any liability arising out of errors or omissions which may be contained in said document, or for errors of judgement, fault or negligence committed by personel of the Society or its Agents in the establishment or issuance of this document, and in connection with any activities for which it may provide.

Toute personne qui n'est pas partie au contrat aux termes duquel ce document est délivré ne pourra engager la responsabilité du Bureau Veritas pour les inexactitudes ou omissions qui pourraient y être relevées ainsi que pour les erreurs de jugement, fautes ou négligences commises par le personnel de la Société ou par ses agents dans l'établissement de ce document et dans l'exécution des interventions qu'il comporte.

STATEMENT OF COMPLIANCE No: GDA0/EMC/20180823101313

NAME OF SHIP: ARKLOW MUSE

BV REGISTER: 15277H

Additional remarks (if any):

	COMPLIANCE No: GDA0/EMC/20180823101313 ARKLOW MUSE 15277H	
See attached lis	t of Classes/Products in annex.	

APPENDIX 1 TO STATEMENT OF COMPLIANCE

No LDR0/MMO/20150608132849

LIST OF CARGOES

All cargoes categorized into Group A of the IMSBC All cargoes categorized into Group C of the IMSBC The following cargoes categorized into Group B of the IMSBC

CARGO SHIPPING NAME	UN No	CLASS	Cargo Hold No
ALUMINIUM FERROSILICON POWDER	1395	4.3	
ALUMINIUM NITRATE	1438	5.1	
ALUMINIUM REMELTING BY-PRODUCTS, ALUMINIUM SMELTING BY-PRODUCTS, ALUMINIUM SALT SLAGS, ALUMINIUM SKIMMINGS, SPENT	3170	4.3	
CATHODES, SPENT POTLINER of ALUMINIUM DROSS			
ALUMINIUM SILICON POWDER, UNCOATED	1398	4.3	
AMMONIUM NITRATE	1942	5.1	
AMMONIUM NITRATE BASED FERTILIZER	2067	5.1	
AMMONIUM NITRATE BASED FERTILIZER	2071	9	
BARIUM NITRATE	1446	5.1	
BROWN COAL BRIQUETTES		MHB	
CALCIUM NITRATE	1454	5.1	
CASTOR BEANS of CASTOR FLAKE OF CASTOR MEAL OF CASTOR POMACE	2969	9	
CHARCOAL		MHB	
COAL		MHB	
COPRA (dry)	1363	4.2	
FERROPHOSPHORUS		MHB	
FERROUS METAL BORINGS, CUTTINGS, TURNINGS or SHAVINGS	2793	4.2	
FLUORSPAR		MHB	
IRON OXIDE, SPENT or IRON SPONGE, SPENT	1376	4.2	
LEAD NITRATE	1469	5.1	
LIME (UNSLAKED)		МНВ	
LINTED COTTON SEED		MHB	
MAGNESIA (UNSLAKED)		MHB	
MAGNESIUM NITRATE	1474	5.1	
METAL SULPHIDE CONCENTRATES		MHB	
PEAT MOSS		MHB	
PETROLEUM COKE (calcined or uncalcined)		МНВ	
PITCH PRILL		МНВ	
POTASSIUM NITRATE	1486	5.1	
PYRITES, CALCINED		MHB	
SAWDUST		MHB	
SEED CAKE, containing vegetable oil a) mechanically expelled seeds, containing more than 10% of oil or more than 20% of oil and moisture combined	1386	4.2	
SILICOMANGANESE		МНВ	
SODIUM NITRATE	1498	5.1	

SODIUM NITRATE AND POTASSIUM NITRATE MIXTURE	1499	5.1	
SULPHUR (crushed lump and coarse grained)	1350	4.1	
TANKAGE		MHB	
VANADIUM ORE		МНВ	
WOODCHIPS		MHB	
WOOD PELLETS		МНВ	
ZINC ASHES	1435	4.3	

Additional remarks (if any):

A. New Individual schedules of solid bulk cargoes (Group B)

ALUMINA HYDRATE

ALUMINIUM SMELTING / REMELTING BY-PRODUCTS, PROCESSED

CLINKER ASH, WET

COAL TAR PITCH

GRANULATED NICKEL MATTE (LESS THAN 2% MOISTURE CONTENT)

SOLIDIFIED FUELS RECYCLED FROM PAPER AND PLASTICS

WOOD TORREFIED

Amendments to test and Sampling procedures for cargoes that may liquefy

C. AMMONIUM NITRATE-BASED FERTILIZER UN 2071 / AMMONIUM NITRATE-BASED FERTILIZER UN 2067

Amendment to the provisions for monitoring and control of the temperature when stowed immediately adjacent to any tank, double bottom or pipe containing heated fuel oil.

As an example, the following means to monitor and control the temperature in the heated fuel oil tank is acceptable when it:

- provide a continuous reading
- provide an alarm in case of temperature goes off limits (50°C)

(Preferably from a manned control station)

An alternative option is to isolate/disconnect the fuel oil heating coils when carrying the product.

In case of other alternative means to monitor and control the temperature of the FO tanks, these have to be submitted to concerned LPO, in coordination with CM.

D. AMMONIUM NITRATE UN 1942

Amendment to the provisions regarding to stowage and segregation.

This cargo shall not be loaded in cargo spaces adjacent to fuel oil tank(s), unless heating arrangements for the tank(s) are disconnected and remain disconnected during the entire voyage."

Mean to disconnect the fuel oil heating coils when carrying the product shall be provided

APPENDIX 1 TO STATEMENT OF COMPLIANCE LIST OF CARGOES

STATEMENT OF COMPLIANCE No :

NAME OF SHIP : ARKLOW MUSE

BV REGISTER: 15277H

Caption used in the next table(s) for the camage of goods

Y indicates CARGO ALLOWED X indicates NOT ALLOWED

CARGO SHIPPING NAME	UN No	CLASS	GROUP	1	2	3	14
Alfalta			C	Υ,	Y 1	X.5.	Y. t
Alumina			C	Y	31	:y	39
Alumina hydrate		MHB	A and B	Ÿ	Y	Y	×
Alumina silica			C	Y	у	Y	¥
Alumina silica, pellets			C	¥	Y	Y	٧
Alumina, calcinated			C	Y	Y	Υ	Ψ
Aluminium Ferrosilicon powder	1395	4.3 sub 6.1	В	Y 2 3	Y = 3	Y 2 7	Υ ,, ,,
Aluminium fluoride			А	γ	Y	Y	Ÿ
Aluminium nitrate	1438	5.1	В	Y.	Y	Y	Y
Aluminium silicon powder, uncoated	1398	4.3	В	Y 2 3	Y 2. 1	V 2 3	Yas
Aluminium smelting tremelting by products, processed		MHB	A and B	Y _{f 4}	Yza	Y 2 #	Y.2.4
Aluminium smelting by-products or aluminum remelting by products	3170	43	В	Y 2 3	Y 2 3	Y 2:3	Y23
Ammonium nitrate	1942	5.1	В	Y 7.5	Y _{2 L}	Y23	Y 2 5
Ammonium nitrate based fertilizer	2067	5.1	8	Yzs	Yza	Y 2 5	Y 2.5
Ammonium nitrate based fertilizer	2071	g	В	Yze	Y 7 n	Y 2 6	Y 2 6
Ammonium nitrated based fertilizer (non hazardous)			C.	Ÿ	Υ	Y	У
Ammonium sulphate			C	3.YE	Y	Y	Y
Amorphous sodium silicate lumps		MHB (CR)	В	Y	Y.	Y	190
Antimony ore and residue			C	Y	Y	Y	Y
Barityes			c	4	Y	¥	Y
Barium nitrate	1446	5.1 sub 6.1	B	Y	Y	Y	Y
Bauxite			C	¥	Y	Y	Y
Biosludge			C	Y.	Y	Y	4
Borax (pentahydrate crude)			C.	Y	Y	Y	У
Borax, anhydrous			c	Y	(Y)	Y	Y
Borie acid		MHB(TX)	₽	+	Y	Y .	Y
Brown coal briquettes		MHB	В	Υ.,	Y.,	Y.;	Y 2
Calcium nitrate	1454	5.1	В	Y	Y	Y	Y
Calcium nitrate fertilizer			c	Y	Y	Y	Y
Carborundum			C	Y	Y	Y	Y
Castor Beans or castor meal or castor pomace or castor flake	2969	9	В	Υ.,	Y. ₇ .	Υ,	Y 7
Cement			c	X	¥	Ϋ́	Y

BV REGISTER : 15277H

CARGO SHIPPING NAME	DN No	CLASS	GROUP	1	2	3	4
Cement clinkers			c	Y	Y	Y	Y
Chamotte			C	Υ	Y	Y	Y
Charcoal		MHB	В	Y	Yx	Υn	V _B
Chemical gypsum			A	¥	Y	Y	Y
Chopped rubber and plastic insulation			С	Yo	Ya	Yw	Υg
Chrome pellets			c	٧	Ÿ	v	¥
Chromite ore			C	γ	Y	¥	Ý
Clay			C	9	Y	Y	Ý
Clinker ash		МНВ	A and B	Y	9. 9 y	y	Y
Coat		MHE	B(and A)	Υ.,	Y.,	Υ :	Υ,
Coal sturry			Д	γ	Y	Y	Y
Coal far pitch		WHB	B	Y	Y	v	Y
Coarse chopped tyres		500 S (100 S)	C	Y 10	Y 10		
Coarse iron and steel stag and its mixture			c	A.		Y 10	Y 10
Cake			5	Ý	Y	Y	Y
Cake breeze				Ý	¥	×	×
Colemanite			A C	Y	Y	ж.	*
Copper granules			c	, i	Ý	Y	χ.
Copper matte			0	y.	Y.	Y	Υ.
Copper stag			A	S Y	Ý		Y
Copra (dry)	1363	4.2	В	Yit	Y 44	Y 11	Y
Crushed carbon anodes			C	ν.	Y		Y 11
Cryolite			c	Y	ě.	Y	Y
Diammonium Phosphate (D.A.P)			C	Y		Y	Y
Direct reduced iron (A) Briquettes, hot-moulded		МНВ	В		Y	Y	Y
Direct reduced iron (B) Lumps, pellets, cold-				Y2 17	A 5. 13	Y 2 12	Y 2 12
moulded briquettes		MHB	В	Y 2 /3	A 5 17	Y = ts	Y 2 11
Direct reduced iron (C) (By-products fines)		MHB	В	Y 2 13	Y 2 13	Y _{2.11}	Y 2 12
Distillers dried grains with solubles			С	Y	y.	Y	Y
Dolomite			C	Y	Y	Y	Y
Fefspar lump			c	Y	Y	Y	Υ
Ferrochrome			C	Y	Y	Y	Y
Perrochrome, exothermic			C	Y	Y	Y	У
Ferromanganese			C	Y	(Y)	Y	Y
Ferronickel			С	Y	. Y.	Y	Υ
Ferrophosphorus (including briquettes)		MHB	8	Y 2	Y z	Y 2	Υg
Ferrosilicon with 25% to 30% silicon or 90% or more silicon (including briquettes)		MHB	В	Y 2.15	Y 2 15	Y _{2.15}	Y _{2 (5}
Ferrosilicon with 30% or more but less than 90% silicon (including briquettes)	1408	4 3 sub 6, i	В	Y 2 14	Y 2 14	Y _{2.16}	Y 2.14
Ferrous metal borings, shavings, turning or cuttings	2793,	4.2	8	٧	Υ	Y	Y

BV REGISTER: 15277H

LWHI WAR AND							
CARGO SHIPPING NAME	UN No	CLASS	GROUP	3	2	3	4
Forrous sulphate heptahydrate			C	Y	Y//	X	Y
Fertilizers without nitrates (non-hazardous)			C	Y	Y	Y	:Y
Fish (in bulk)			A	Y	Y	Y	Y
Fishmeal (fishcrap), stabilized	2216	9	В	Y to	Y 16	Y 16	Y. 10.
Fluorspar		MHB	A and B	Υ	Y	Υ'	Y
Fly ash, dry			C	Y	Y	Y	Y
Fly ash, wet			A	Y	Y	Y	Y
Glass cultet			C	Υ	γ	Y	Υ
Grain screening pellots			C	Y 17	Y 17	Y 17	Y 17
Granular ferrous sulphate			C	¥	Υ	Υ	Υ
Granulated nickel matte (less than 2% moisture content)		MHB	В	¥	¥	Υ	Υ
Granulated slag			C	Y	Y	¥	Ÿ
Granulated Tyre rubber			C	Υ 18	Y 18	Y 18	Y 18
Gypsum			C	¥	¥	Y	Y
Gypsum granulated			r:	Ÿ	Y	Y	٧
Ilmenite (rock)			c	¥	Ÿ	Y	Y
Ilmenite (upgraded)			A	¥	Y	¥	Y
Ilmenite clay			А	Y	Y	y	¥
Ilmenite sand			A or C	y.	Y	¥.	Y
fron and steel slag and its mixture			A	Y	×	Y	Y
Iron ore			C	Y	Y	Y	Y
Iron ore fines			A	Y	Y	Y	Y
fron ore pellets			C	Ý	Y	Y	ý.
fron oxide technical			Д,	Υ	Ÿ	Ÿ	Y
Iron oxide, spent or Iron sponge, spent	1376	4.2	В	Y 19	Y 10	Y 19	Y 19
Iron sinter			c	4	¥	Y	Y
Ironstone			è	Y	Y	Y	Y
Labradorite			C-	Y	Y	Y	y
Lead nitrate	1469	5.1 sub 6.1	В	Y	Y	Y	Y
Lead ore			c	Y	Y	Y	Y
Lime (unslaked)		MHE	В	Y	Y	Y	Y
Limestone			c	4	v	Y	Y
Linted cotton seed with no more than 9% moisture and not more than 20.5% oil		MHB	В	Y	Υ	Y	Y
Magnesia (deadburned)			С	Y 20	Y 20	Y 20	Y 20
Magnesia (unslaked)		MHB	В	γ.	ν.	V	φ.
Magnesite, natural			0.	Y	Y	y	Y
Magnesium nitrate	14/4	5.1	В	Y	Y	Y	· ·
Magnesium sulphate fertilizers		1.560	C	Y	Y	y	y
Manganese componenent ferroalloy slag			C	¥	Y	Y	Y
			77	7	1.2	0.70	Υ.

BV REGISTER: 15277H

CARGO SHIPPING NAME	UN Na	CLASS	GROUP	1	2	3	4
Manganese ore			C	+	Y	٧	Y
Manganese ore fines			A	4	Y	Y	Υ
Marble chips			C	γ	Y	Y	Y
Metal sulphide concentrate		MHB	A and 8	γ	Y	Y	Υ
Mineral concentrates			A	V.	y	Y	Y
Monoammonium phosphate (M.A.P)			C	Y	y	Y	Υ
Nickel ore			A	. Y.	(Y)	y	Υ
Peanuts (in shell)			c	Ψ.	Y	Y	Y
Peal moss		WHB	A and B	4	Y	٧	4
Pebbles (sea)			G	+	'n	Y	Υ
Pellets (concentrate)			C	Y	Y	¥	Y
Perlite rock			С	+	y.	Y	Υ
Petroleum coke (calcined or uncalcined)		MHB	В	Y	y	Y	Υ
Phosphate (defluorinated)			C	19	V	Α:	Y
Phosphate rock (catcinated)			С	Y	Υ.	(%)	Υ
Phosphate rock (uncalcinated)			С	*	Y	Y	Y
Pig iron			c	4	¥	4	٧
Pitch prill		MHB	В	Y	Y	Y	Υ
Potash			C	¥	Y	¥	Υ
Potassium chloride			C	7	4	4	Υ
Potassium nitrate	1485	51	В.	Y	У	Υ.	Y
Potassium sulphate			C	*	Y	Y:	Y
Pumice			C	Y	Y	¥	Y
Pyrite (containing copper and iron)			C	¥	Y	¥	Y
Pyrites, calcinated (calcinated pyrites)		MHB	A aind B	Υ	Ψ.	٧	Y
Pyrophyllite			G.	γ	Y	Y	Υ
Quartz			C	γ	Y	Y	Υ
Quartzite			C	Y	Y	Y	Y
Radioactive material, low specific activity (LSA-1), non fissile or fissile-excepted	2912	7.	В	X	×	×	х
Radioactive material, surface contaminated objects (SCO-I), non fissile or fissile-excepted	2913	7	В	×	х	х	х
Rasorite (anhydrous)			c	Y	Y	Y	У
Rutile sand			c	Y	4	Y	. 4
Salt			C	Y	Y	Υ	¥
Salt cake			C	Y	Y	Y	Y
Salt rock			G	Y	Y	Y	γ
Sand			C	Υ	Y	Υ	Y
Sand, heavy mineral			٨	Y	Y	Y	y
Sawdust		MHB	В	Y 21	Y 71	Y 21	Y 21
Scale generated from the iron and steel making process			Ä	Y	Υ	У	Y
NAMES (1878)							

BV REGISTER: 15277H

CARGO SHIPPING NAME	UN No	CLASS	GROUP	1	2	3	4
Scrap metal			C	Y	Y	Y	Y
Seed cake (non-hazardous)			C	Y	Y	Y	Υ
Seed cake with not more than 1.5% pil and not more than 11% moisture	2217	4.2	В	$_{2.22}$	Y 2 22	Y 2 22	Y 2, 22
Seed cake, containing vegetable oil (a), mechanically expelled seeds, containing more than 10% of oil or more than 20% of oil and moisture combined	1386	4.2	В	٧	Y	Ý	Y
Seed cake, containing vegetable oil (b) solvent extractions and expelled seeds, containing not more than 10% of oil and when the amount of moisture is higher than 10%, not more than 20% of oil and moisture combined	1386	42	В	Y 2 31	Y j . ₂₇	Y 2 72	Y 7.22
Silicomanganese (fow carbon)		MHB	В	Y 2:20	Y 2 21	Y 2, 23	Y 2 21
Silicon slag			C	Y	¥	×	Y
Soda ash (Dense and light)			C	Y	Y	Y	у
Sodium nitrate	1498	51	8	Y	Y	Υ	Y
Sodium nitrate and potassium nitrate mixture	1499	5.1	B	¥	¥	Y	Y
Solidified fuels recycled from paper and plastics		MHB	В	Y 24	4 24	4 24	Y 24
Spodumene (upgraded)			A	Y	Y	Y	Ÿ
Stainless steel grinding dust			С	¥	¥	Y	Y
Stone chippings			0	×	¥	Y	Y
Sugar			C	×	Y	*	Y
Sulphate of potash and magnesium			c	Y	×	Y	Y
Sulphur (crushed lump and coarse grained)	1350	4.1	Η	Y 2 25	Y 3.25	Y 2 25	Y 2 25
Sulphur (formed, solid)			C	×	Y	Y	Y
Superphosphate			c	Y	Y	Υ	Y
Superphosphate (triple, granular)			C	Y	¥	Y	×
Tacanite pellets			C	Y	Ÿ	Ÿ	Y
Tale			C	Υ	¥	Y	y
Tankage		MHB	В	Y	Y	Y	Ÿ
Tapioca			C	8.	8	Y	Υ
Urea			C	Y	Y	8	Ψ.
Vanadium ore		MHB	8	'n	Y	Y	8
Vermiculite			C	¥ 26	Y 240	You	Y 26
White quartz			С	3.90	Y	Y	Υ
Wood pellets containing additives and/or binders		MHB(WF)	В	Y	Y	Y	Y
Wood pellets not containing any additives and/or binders		MHB(OH)	В	Υ	Y	Y	Y
Wood produts -general		MHB	В	Y	Y	Y	Y
Wood torrefied		MHB	В	Y	Y	Υ	Y
Woodchips		MHB	B	(10)	Y	Y.	Y
Zinc ashes	†435	4.3	8	Υ2	Y 2	Yz	Y2
Zinc slag			A	(9)	Y	Y	Y

BV REGISTER 15277H

CARGO SHIPPING NAME	UN No	CLASS	GROUP	1	2	3	4
Zircon kyanite concentrate			A	γ	8	Υ	Υ
Zirconsand			C	*	Y	Y	Y

BV REGISTER: 15277H

Notes applicable for this document

- (1) Prior to loading of this cargo, a certificate shall be provided by a competent authority or shipper stating that the material as shipped does not meet the requirement for Seed case.
- [2] In areas which are classified as hazardous, electrical equipment which is not essential for the safety and operation of the ship and which is not of a type approved for use in the hazardous area shall be:
 - completely disconnected by appropriate means other than fuses at a point external to the space
 - protected against unauthorized re-connection
- (3) Prior to loading this cargo a certificate shall be provided by the manufacturer in shipper stating that, after manufacture, the material was stored under cover, but exposed to the weather in the particle size shipped, for not less than 3 days prior the shipment.
- (4) Prior to loading this cargo a weathering perforate shall be provided by the manufacturer or shipper stating that lafter manufacturer, the material was stored under cover, but exposed to the weather in the particle size shipped, for not less than 4 WEEKS prior the shipment.
- (5) Prior to loading, the shipper shall provide the master with a certificate signed by the shipper stating that all the relevant conditions of the cargo required by this code including its individual schedule have been met. In addition, prior to loading, the shipper shall provide the master with a certificate stating that the resistance to detonation of this material is in compliance with this requirements.
- (6) This cargo shall only be accepted for loading when, as a results of testing in the trough test, its liability to self-sustaining decomposition shows decomposition rate not greater than 0.25m/h
- (7) Castor mean, castor pomace and castor flakes shall not be carned in bulk
- (8) The manufacturer or shipper shall give the master a certificate stating that the cargo is not class 4.2 in accordance with the results of the fest approved to the competent authority. The certificate shall also state that this cargo has been weathered for not less than 13 days. This cargo shall only be accepted for loading when the actual moisture content of the cargo is not more than 10%.
- (9) Prior to stopment, is certificate shall be given to the master by the shipper stating that this cargo consists of clean plastic and rubber material only.
- (10) Prior to shipment, a certificate shall be given to the master by the shipper stating that this cargo is free of oily products or oily residue and has been stored under cover but in the open air for not less than 15 days prior shipment.
- (11) This cargo shall only be accepted for loading when the cargo has been weathered for at least one month before shipment or when the shipper provides the master with certificate issued by a person recognized by the competent authority of the country of origin stating that the moisture content of the cargo is not more than 5%.
- (12) The shipper shall provide the muster with a certificate issued by a competent person recognized by the national administration of the port of loading stating that the cargo, at the time of loading, is suitable for shipment and that it conforms with the requirements of IMSBC Code; that the quantity of times and small particles (up to 6.35 mm in size) is no more than 5% by weight, the maisture content is less than 1.0% and the temperature does not exceed 65°C.
- Prior to loading this Cargo, the shipper shall provide the master with a certificate issued by a competent person recognized by the national Administration of the port of loading stating that the cargo, at the time of loading, is suitable for shipment, and that it conforms with the requirements of IMSBC Code, that the quantity of fines and small particles is no more than 5% by weight, that the moisture content is less than 0.3%, and that the temperature does not exceed 65°C. This certificate shall state the date of inactidations for each lot of cargo to be loaded in order to meet the loading criteria in regards to ageing and material temperature. Provision shall be made to introduce a dry next gas at tank-top level so that the ment gas purges the air from the cargo and fills the free volume above prior to loading and to maintain the oxygen concentration below 5% throughout the volyage in accordance with the requirements of IMSBC.
- (14) The manufacturer or the shipper shall provide the master with a certificate stating that, after manufacture, the cargo was stored under cover, but exposed to dry weather for not less than three days prior to shipment.
- (15) The manufacturer or the shipper shall provide the master with a certificate stating that, after manufacture, the cargo was stored under cover, but exposed to open air for not less than three days prior to shipment.
- (16) The shapper shall provide the master with a certificate issued by a person recognized by the competent authority of the country with the information requested in IMSBC (mosture content, fat content, date of production...)
- (17) A certificate from a person recognized by the competent authority of the country of shipment shall be provided by the shipper to the master, prior to loading, confirming that the oil and moisture contents as described in the schedule have been met.
- (18). Prior to shipment, a certificate shall be given to the master by the shipper stating that this cargo consists of clean rubber only
- (19) Prior to loading, the shipper or the manufacturer shall provide the master with a certificate stating that the cargo has been cooled and then weathered for not less than 8 weeks prior to shipment.
- (20) Prior to loading, the shipper or the manufacturer shall provide the master with a declaration stating that the cargo has been sufficiently heat-treated and is ready for loading
- (21) Prior to loading this cargo, the shipper shall provide the master with a certificate stating that the cargo is clean, dry and free from oil
- (27) This cargo shall only be accepted for loading when the cargo is substantially free from flammable solvent and a certificate from a person recognized by the competent authority of the country of shipment specifying the oil content and moisture content is issued.
- (23) The manufacturer or the shipper shall provide the master with a certificate stating that, after manufacture, the cargo was stored under cover, but exposed to open air for not less than three days prior to shipment.
- (24) The manufacturer or shipper shall give the master a certificate stating that the cargo is not class 4.2
- (25) Fine grained sulphur (flower of sulphur) shall not be transported in bulk
- (26) Prior to leading, a certificate based on test shall be provided by the manufacturer or shipper stating that the asbestos content is less than 1%

Space identification

- ± CARGO HOLD I
- 2 CARGO HOLD 2
- 3 CARGO HOLD 3
- 8 CARGO HOLD 4